

TECHNICAL DATA SHEET



TROJAN® NB UNIVERSAL

Superprime® Cord Sensitive Booster

Properties

SDS
#1108

Density	g/cc avg	1.60
Velocity	m/sec	7,800
	ft/s	25,600
Detonation Pressure	Kbars	245
Water Resistance	6 months with no loss of sensitivity	
Shelf Life Maximum	5 years from date of production	
Maximum Usage Temperature	66°C / 150°F	

All Dyno Nobel Inc. energy and gas volume values are calculated using PRODET™ the computer code developed by Dyno Nobel Inc. for its exclusive use. Other computer codes may give different values.

Hazardous Shipping Description

- Boosters, 1.1D, UN 0042 PG II



PRODUCT DESCRIPTION

TROJAN NB Universal cast booster is a detonator and detonating cord sensitive, high density, high energy, molecular explosive available in three sizes. TROJAN NB Universal is manufactured using a homogeneous mixture of pure pentolite for superior performance, reliability, consistency and durability and is especially designed to optimize initiation of all cast booster sensitive and/or detonator sensitive explosives. Each TROJAN NB Universal cast booster is manufactured with two internal through-tunnels and a detonator well for easy use with either detonating cord or commercial detonators. The bright yellow container enhances visibility on the bench and minimizes misplaced charges.



APPLICATION RECOMMENDATIONS

- **ALWAYS** use Dyno Nobel PRIMACORD® brand detonating cord with TROJAN NB Universal cast boosters for best results.
- **NEVER** use detonating cord with a coreload less than (5.3 g/m or 25 gr/ft) for single pass threading.
- Extremely low temperatures do not affect the performance of cast boosters with commercial detonators. Low temperatures do affect detonators and detonating cord. Be certain your initiation system is suitable for your application in extremely low temperatures. Cast boosters are more susceptible to breakage during handling in extremely cold temperatures.

Product Disclaimer: Please see reverse side.

DYNO®
Dyno Nobel

TECHNICAL DATA SHEET



TROJAN® NB UNIVERSAL

Superprime® Cord Sensitive Booster

Properties Cont.

Packaging

Unit Weight		Unit Dimensions				Case Quantity	Gross Weight/Case	
g	oz	Length		Diameter			kg	lbs
		cm	in	cm	in			
350	12	11.9	4.7	5.0	2.0	49	16.8	37.0
400	14	11.9	4.7	5.5	2.2	40	16.8	37.0
450	16	11.9	4.7	5.8	2.3	36	16.5	36.4
900	32	12.9	5.1	7.9	3.1	18	16.9	37.2

Note: All weights and dimensions are approximate.


Case Dimensions

42 x 34 x 13 cm

16 5/8 x 13 3/8 x 5 1/4 in

APPLICATION RECOMMENDATIONS - continued

- **NEVER** force the detonator into the through-tunnel, the detonator well or otherwise attempt to clear these areas if obstructed. If the through-tunnel or detonator well does not accommodate the detonator or detonating cord, do NOT use the booster. Notify your local Dyno Nobel representative.
- **ALWAYS** use Dyno Nobel recommended PRIMACORD detonating cord threading procedures. When PRIMACORD 4 (3.6 g/m; 18 gr/ft) detonating cord is used, ensure the detonating cord is looped and double-passed through the large through tunnel (see Recommended Lacing Method below).



RECOMMENDED LACING METHOD

TRANSPORTATION, STORAGE AND HANDLING

- Dyno Nobel cast boosters must be transported, stored, handled and used in conformity with all federal, state, provincial and local laws and regulations.
- For maximum shelf life (5 years), Dyno Nobel cast boosters must be stored in a cool, dry, well ventilated magazine. Explosive inventory should be rotated. Avoid using new materials before the old.

ADDITIONAL INFORMATION – Visit dynonobel.com for Brochures and Case Studies related to this product.

Product Disclaimer: Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

DYNO®
Dyno Nobel